

LED Flood Light

- High Powered Slim LED Flood Light
- 3 Year Warranty
- 50,000 hours average usage
- 100,000 switching cycles
- CCT 6000K Cool White
- Pre-wired 1 metre cable
- A+ Energy rated

COOL
WHITE

ENERGY
SAVING

BEAM ANGLE
120°



Model No.	Description	Dimension (mm)	Voltage	Chip	IP grade	PF	Lumen	CRI	Lifetime	CCT (Color temperature)	Wire
AURIGA-10	Die-casting aluminum with steel glass cover	124x110x37	220V 50-60Hz	Bridgelux ChipSMD2835 20PCS	IP66	>0.9	1000	80Ra	50,000 hours	Cool White 6000K	1M
AURIGA-20	Die-casting aluminum with steel glass cover	146x126x37	220V 50-60Hz	Bridgelux ChipSMD2835 40PCS	IP66	>0.9	2000	80Ra	50,000 hours	Cool White 6000K	1M
AURIGA-30	Die-casting aluminum with steel glass cover	195x165x40	220V 50-60Hz	Bridgelux ChipSMD2835 60PCS	IP66	>0.9	3000	80Ra	50,000 hours	Cool White 6000K	1M
AURIGA-50	Die-casting aluminum with steel glass cover	230x195x57	220V 50-60Hz	Bridgelux ChipSMD2835 100PCS	IP66	>0.9	5000	80Ra	50,000 hours	Cool White 6000K	1M
AURIGA-100	Die-casting aluminum with steel glass cover	297x250x57	220V 50-60Hz	Bridgelux ChipSMD2835 200PCS	IP66	>0.9	10000	80Ra	50,000 hours	Cool White 6000K	1M
AURIGA-150	Die-casting aluminum with steel glass cover	355x290x57	220V 50-60Hz	Bridgelux ChipSMD2835 300PCS	IP66	>0.9	15000	80Ra	50,000 hours	Cool White 6000K	1M