

LED Flood Light

With Sensor



- High Powered Slim LED Flood Light
- 3 Year Warranty
- 50,000 hours average usage
- 100,000 switching cycles
- CCT 6000K Cool White
- Pre-wired 1 metre cable
- A+ Energy rated

COOL
WHITE

ENERGY
SAVING

BEAM ANGLE
120°



Model No.	Description	Dimension (mm)	Voltage	Chip	IP grade	PF	Lu- men	CRI	Lifetime	CCT (Color temperature)	Wire	PIR RANGE
AURIGA-S10	Die-casting aluminum with steel glass cover	124X165X47	220V 50-60Hz	Bridgelux Chip SMD2835 20PCS	IP66	>0.9	1000	80Ra	50,000 hours	Cool White 6000K	1M	3-10m
AURIGA-S20	Die-casting aluminum with steel glass cover	146X181X47	220V 50-60Hz	Bridgelux Chip SMD2835 40PCS	IP66	>0.9	2000	80Ra	50,000 hours	Cool White 6000K	1M	3-10m
AURIGA-S30	Die-casting aluminum with steel glass cover	195X220X50	220V 50-60Hz	Bridgelux Chip SMD2835 60PCS	IP66	>0.9	3000	80Ra	50,000 hours	Cool White 6000K	1M	3-10m
AURIGA-S50	Die-casting aluminum with steel glass cover	230X250X57	220V 50-60Hz	Bridgelux Chip SMD2835 100PCS	IP66	>0.9	5000	80Ra	50,000 hours	Cool White 6000K	1M	3-10m